



### 技术参数:

#### 插芯:

- 插针数: 8+PE
  - 额定电流: 10A
  - 额定电压: ~50V/-250V
  - 额定脉冲电压: 0.8kV
  - 污染等级: 3
  - 依据UL/CSA的额定电压: 50V
  - 额定电压(直流电压): 120V
  - 绝缘电阻:  $>10^{10}\Omega$
  - 材料: 聚碳酸酯
  - 颜色: RAL 7032 (浅灰色)
  - 温度范围:  $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
  - 依据UL 94的阻燃等级: V0
  - 可插拔次数:  $>500$
- #### 插针:
- 接线方式: 冷压连接
  - 材料: 铜合金
  - 表面处理:
    - 镀银
    - 镀金
  - 接触电阻:  $<3\text{m}\Omega$
  - 线径范围: 0.14-2.5mm<sup>2</sup>(26-14 AWG)
  - 工具:
    - 冷压钳: TL02G
    - 送针器: TL00

### Technical specification:

#### Inserts:

- No. of contact: 8+PE
  - Rated current: 10A
  - Rated voltage: ~50V/-250V
  - Rated impulse voltage: 0.8kV
  - Pollution degree: 3
  - Rated voltage acc.to UL/CSA: 50V
  - Rated voltage(direct voltage): 120V
  - Insulation resistance:  $>10^{10}\Omega$
  - Material: polycarbonate
  - Colour: RAL 7032(light grey)
  - Temperature range:  $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
  - Flammability acc.to UL 94: V0
  - Mating cycles:  $>500$
- #### Contacts:
- Terminal: crimp terminal
  - Material: copper alloy
  - Surface:
    - Hard-silver plated
    - Hard-gold plated
  - Contact resistance:  $<3\text{m}\Omega$
  - Wire gauge: 0.14-2.5mm<sup>2</sup>(26-14 AWG)
  - Tools:
    - Crimp contact tool: TL02G
    - Contact removal tool: TL00

						表面处理 Finish	-			图号 Drawing No.	-
						材料 Material	-			产品代号 Part Code	HD-008-MC
标记 Mark	数量 Number	变更描述/Description			签名 Signature	日期 Date				产品料号 Part No.	1250080100001
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	-
绘图 Drawn	BQ LUO	18.10.2010	标准化 Stand.	-	-	1:1	V1.0	7.6g	-		
审核 Checked	P RAO	18.10.2010									
工艺 Process	-	-	批准 Approved	YY LIN	18.10.2010	All Dimensions in mm Original Size DIN A 4			厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD		